

# GigaSwitch V5 7 Port 54VDC MED Series

## LANactive 7 Port Managed Full Gigabit Ethernet FTTO Switch

- 3 Uplink Ports (2x SFP and 1x RJ45)
- 4 Isolated User Ports (4kV and 2MOPP)
- Efficient Energy Management
- Memory Card Slot
- Input Voltage Range 46 ... 57V DC

## Description

Aginode LANactive GigaSwitch V5 MED series is designed for the installation in Fibre to the Office (FTTO) networks. The latest generation of FTTO switches is equipped with a state-of-the-art network processor and provides enhanced performance, security and redundancy functionality.

### Galvanic Isolation

The GigaSwitch V5 MED series is equipped with integrated network isolators at the user ports to have a minimum withstand voltage of 4 kV and 2 MOPP according to EN60601-1. They prevent unwanted voltage differences between devices over the network cabling connected to the user ports.

### 7 Port Version

The GigaSwitch version with seven ports is part of the latest V5 series. This special variant with three uplink ports allows a redundant connection of the GigaSwitch via fibre optic. The RJ45 uplink can be used for connecting an additional Wireless LAN Access Point. All uplinks support Link Aggregation for providing redundancy and double bandwidth up to 2Gbps.

### Snap-In Installation

The very compact design of the GigaSwitch allows a tool-less snap-in installation into the standard 45 mm cable duct systems or floor boxes without special mounting accessories.

### Memory Card

The optional memory card automatically saves the complete current configuration and firmware of the device. In case of failure, this feature allows an easy exchange of the hardware without additional configuration. In addition, each memory card can be delivered with its own MAC address that is adopted by the switch.

### Switch Management and Zero-Touch Configuration

Aginode LANactive Manager allows a simple and secure configuration of all device parameter of the GigaSwitch series. With the LANactive Manager a larger number of GigaSwitches can be managed and monitored at the same time. In combination with Aginode Zero-Touch Configuration, the LANactive Manager allows automatic distribution of configurations and firmware updates. A pre-configuration of the switches is not necessary.



Made in Germany

## LANactive

## Standards

### IEC 60601-1

- IEEE 802.3
- IEEE 802.3u
- IEEE 802.3ab
- IEEE 802.3z
- IEEE 802.3x
- IEEE 802.1AB
- IEEE 802.1D
- IEEE 802.1Q
- IEEE 802.1X
- IEEE 802.1AX
- IEEE 802.3ad



Real-Time OS  
Yes



PoE/PoE+  
Yes



Compact design  
45x90mm



Noiseless  
Yes



Fast Installation  
Yes



Redundancy  
Yes



Operating T°  
0 ... 45 °C



Electromagnetic Shielding  
Yes

**Connect Com AG**  
Wahligenstrasse 4A  
6023 Rothenburg  
Schweiz  
+41 41 854 00 00  
info@ccm.ch  
www.ccm.ch

**Connect Com SA**  
Route des Avouillons 30  
1196 Gland  
Suisse  
+41 21 804 66 22  
info@ccm.ch  
www.ccm.ch

**Connect Com GmbH**  
Stegweg 36-38  
72622 Nürtingen  
Deutschland  
+49 7022 9607 100  
info@connectcom.de  
www.connectcom.de

# GigaSwitch V5 7 Port 54VDC MED Series

## Hardware Features

Ordering Information	GigaSwitch V5 TP(PSE+) SFP-2VI 54VDC MED	GigaSwitch V5 TP SFP-2VI 54VDC MED
Article Number	902815	902816
Switching Type	Store-and-Forward, self-learning	
Non-blocking Switching Capacity	20Gbps	
Packet Forwarding Rate	2x 1.488Mpps per port	
Max. Frame Size	9,600Bytes	10,240Bytes
Packet Buffer	512kBytes	256kBytes
MAC-Address Table	8k	16k
<b>Interfaces</b>		
User Ports (RJ45)	4x 1000Base-T	
Uplink Ports (SFP)*	2x 1000Mbps	
Uplink Ports (RJ45)	1x 1000Base-T	
RJ45 Ports	Auto-Negotiation, MDI/MDI-X Auto-Cross Over and Auto-Polarity	
Digital Diagnostics Monitoring Interface	Yes	
Twisted Pair Cable Diagnostic	Yes	
Rotatable Head Module	Yes	
<b>Power over Ethernet</b>		
Number of PoE User Ports	-	
Number of PoE Uplink Ports	1x PSE(PoE+) acc. to IEEE802.3at	-
PoE Mode	30W per Port, Mode A, Pin 1-2/3-6	-
Max. PoE power budget	30W	-
<b>General</b>		
Dimensions [W x H x D]	90mm x 45mm x 69mm	
Installation Depth	35mm	
Material	zinc diecasting / stainless steel	
Colour	Pure White, like RAL 9010	
Ambient Temperature	Operation: 0 ... 45°C, Storage: -20 ... 85°C	
Relative Humidity	20 ... 90% (non-condensing)	
Weight	290g	
MTBF	> 750,000h	
<b>Power Supply</b>		
Input Voltage	46 ... 57V DC (typ. 54V DC)	
Power Consumption	4.3W typ., 5.5W max.	
Heat Output	19Btu(IT)/h	
Connector	3-pin connector (up to 2.5mm <sup>2</sup> ) / (+) (-) (FPE)	
<b>CE - Conformity</b>		
Electro Magnetic Capability Directive	2014/30/EU	
Low Voltage Directive	-	
RoHS 2	2011/65/EU	
Engineering Standards	EN 62368-1, EN 55032, EN 55024, EN 50581	

## Software Features

### Switching Parameters

VLANs	IEEE802.1q with up to 256 Groups
Quality of Service Layer 2	IEEE802.1p Class of Service (4 Queues per Port)
Quality of Service Layer 3	RFC2474/3168 DSCP (4 Queues per Port)
Bandwidth Limitation	Bitrate
Energy Efficient Ethernet	IEEE802.3az
Flow Control	IEEE802.3x
Fabric Attach	Basic Fabric Attach Client Support

### Management

	On-Board High-Performance Management
LEDs	Management, Port Status and Activity, Memory Card
Zero-Touch Configuration	Via LANactive Manager Controller
IP-Address	IPv4, IPv6
DHCP-Client	DHCP, DHCPv6
DHCP Relay Agent	Yes
File Transfer	TFTP, SCP
Console Port	V.24 with Aginode Console Cable
Web-Interface	HTTP, HTTPS
Command Line Interface	SSH, Telnet, V.24
Scripting	Yes
SNMP	SNMPv1, v2c, v3
Syslog	Yes
Discovery Protocols	LLDP (IEEE802.1AB), LLDP-MED (ANSI/TIA-1057), CDP
Time Synchronisation	SNTP
Port Statistics	Detailed per Port

### Redundancy

Redundancy Protocols	STP, RSTP, MSTP, MRP
Link Aggregation	LACP

### Security

Password Protection	Two Access Levels (R/W or R/O)
Authentication via Radius and TACACS+	CLI and LANactive Manager
ACL for Management Interface	Up to 16 Access Control Lists
Portsecurity via MAC-Address	Up to 3 predefined MAC-Addresses
Portsecurity via Radius	IEEE802.1x with MAC Bypass
DHCP Snooping	Yes
Loop and Broadcast Limiter	Yes
Firmware Update	Dual Firmware Image
Configuration-/Reset Button	Yes / Yes
Memory Card	micro SD-Card with own MAC-Address (optionally)

# GigaSwitch V5 7 Port 54VDC MED Series

## Dimensions

