

Installation Power Supplies 54VDC/65W

Features

- Power Supply for Aginode GigaSwitch series
- Full PoE+, IEEE 802.3at, compatibility
- Fanless design
- Output Power: 65 Watts
- Control-LED
- Primary Connection (100-240V AC):
 - Three core wire H03VV cord, 1,5m, pre assembled with insulations screw joint
 - or Schuko connector
- Secondary connection (54V DC):
 - Three core wire H03VV cord, 1m, with pre assembled 3-pin connector
 - or moulded 3-pin connector
- Mutual connection of function earth



LANactive

Hardware specification

Rated input range	100-240V AC 50-60 Hz
Input range	90-265V AC 47-63 Hz
Input current	1.13A at 115V AC 0.67A at 230V AC
Max. input current	1.5A
AC leakage current	Max. 0.25mA at 240V AC input
Max. inrush current	60A at 240V AC, 25°C
Unload standby power	<0.5W
Isolation	1.5kV
Rated output range	54V DC
Max. output current	1.2A
Max. output power	64.8W
Electrical protection	Short circuit, overvoltage and overcurrent protection
Efficiency	Min. 80% Typ. 87%
Weight	225g
Dimensions	120 x 54 x 32 mm
Ambient operating temperature range	0 ... 40°C
Storage temperature range	-10 ... 55°C
Relative humidity	5 ... 90%
Primary cable	Flexible H03VV cable with 3 wires
Secondary cable	Flexible H03VV cable with 3 wires
Cable conductors	0.75mm ² acc. to IEC 60364 Part 5-52 Table 52-5
Safety	CE, EN 60950, IEC 60950*
EMC	EN 55022, EN 55024, GB 9254-1998 (CISPR 22)
Protection	Class II

*The product is suitable for connection to IT power distribution systems providing 100-240V phase to phase voltage

Connect Com AG
 Wahligenstrasse 4A
 6023 Rothenburg
 Schweiz
 +41 41 854 00 00
 info@ccm.ch
 www.ccm.ch

Connect Com SA
 Route des Avouillons 30
 1196 Gland
 Suisse
 +41 21 804 66 22
 info@ccm.ch
 www.ccm.ch

Connect Com GmbH
 Stegweg 36-38
 72622 Nürtingen
 Deutschland
 +49 7022 9607 100
 info@connectcom.de
 www.connectcom.de

